



## Instructions For Installing your Category 1 Receiver Plate RP5522

**Alexander  
EQUIPMENT CO., LLC**

P.O. Box 694  
Greenville, South Carolina 29642  
866.833.1160 Toll Free

Patent Number 5,743,339

Congratulations on your new purchase of the Delta Hook™ Rapid Hitch System™. You will be able to attach your implements without leaving the tractor! Please check the packing list with parts included in the box and notify us of any missing parts. We hope you enjoy your new Delta Hook™ Rapid Hitch System™. We appreciate your business and all comments are welcome!

### To Install Plate to Implement

*For shipping purposes, brackets are shipped upside down on the receiver plate.*

- 1) Remove brackets from Receiver Plate.
- 2) Attach top link tube to top link arm of implement as shown in Figure 1. Several holes are made to allow for adjustment to your implement.
- 3) Reinsert the brackets into channels of Receiver Plate. Bracket should be pointing down and with hole side to implement.
- 4) Align hole of right bracket to hole of implement's bottom arm and secure with 5/8-11x1-1/4" hex bolt and locknut as shown in Figure 2. *Do not slide bracket out more than 3 inches.*
- 5) Repeat step four for the left bracket.

**DUE TO THE SIZE AND WEIGHT OF THE PLATE, WE RECOMMEND TWO PEOPLE  
INSTALL THE RECEIVER PLATE ON THE IMPLEMENT.**


### Items to be installed



Receiver Plate  
RP5522



Right Angle Bracket  
AG2016



Left Angle Bracket  
AG2015



5/8-11x1-1/4" Hex Bolt  
AG2023



5/8-11x1-1/4" Locknut  
AG2012



Lynch Pin  
AG2014



Top Link Pin  
AG2013



Top Link Tube  
AG2010

### Items already installed



Strike Plate  
AG2019



5/8x11x2 Nut  
AG2802



FIGURE 1



FIGURE 2

All hardware is included for installation of your Receiver Plate. If you choose, you may use the existing hardware on your implement.

### To Adjust Locking Pin to Strike Plate.

- 1) With Control Plate and Receiver Plate engaged, adjust strike plate to within 1/16" or less of locking pin as shown in Figure 3.

*As initial break-in could cause excessive clearance, check again after short time of use.*



FIGURE 3



# Instructions For Installing Your Delta Hook™ Rapid Hitch System™ Category 1 Receiver Plate

**INSTALL THE RECEIVER PLATE ON THE TRACTOR.  
DUE TO THE SIZE AND WEIGHT OF THE PLATE, WE RECOMMEND TWO PEOPLE**

When Receiver Plate is installed, it should resemble photo below.



Should you encounter any problems with your Delta Hook™Rapid Hitch System™, please contact us immediately at 866-833-1160, M-F 8:30am—5:30pm e.s.t.